

JED-438

40



CHUCKED LENTA
EINSpannLAENGE 23mm
LONGUEUR D'ENCASTREMENT
LUNGHEZZA DI FISSAGGIO



SPRING DIAGRAM
FEDERDIAGRAMM
DIAGRAMME DE RESSORT
DIAGRAMMA DI MOLLA

STRO
HUB
COUF
CORS

WORKING PRESSURE MAX. 10 bar
BETRIEBSDRUCK
PRESSION D'UTILISATION
PRESSIONE DI ESERCIZIO
THERMAL RANGE OF APPLICATION
THERMISCHER ANWENDUNGSBEREICH -40 °C BIS + 80 °C
GAMME D'APPLICATION THERMIQUE
CAMPO DI APPLICAZIONE TERMICA

AIR
LUFT
AIR
ARIA

*

INDICATION FOR INSTALLATION: STOP MUST BE ARRANGED OUTSIDE OF THE CYLIND.
EINBAUHNWEIS: ANSCHLAG MUSS AUSSERHALB DES ZYLINDERS LIEGEN
INDICATION POUR INSTALLATION: BUTEE DOIT ETRE DISPOSEE AU DEHORS DU CYLIND.
INDICAZIONE DI MONTAGGIO: ARRESTO DEVE ESSERE DISPOSTO FUORI DEL CILINDRO

1) TOLERANCE CLASS APPLIED CROSSMARKE

WABCO

CYLINDER
CYLINDRE
CILINDRO
ARBEITSZYLINDER

421 411 094 0

1/

605