

Product Image



/publicpictures/Produktbild/1173700008.tiff

Master data

Product number:	1173700008
EAN:	4007123685394
Article owner:	Brennenstuhl Tübingen
manufacturer:	Brennenstuhl
Product line:	
Customised:	No
Minimal care:	No
Rejection indicator:	J
Gewählte Vertriebsregion:	De
Gewählte Sprache:	en

Texts

IS4 designation 1/2:

Stativ LED Stahler Dreikopf 13050 T 13500lm, IP54, 5m H07RN-F2X1,0

Short description for the internet:

Brennenstuhl Professional tripod LED construction spotlight three-head 13050 T with 13500lm (LED construction spotlight with 3 individually adjustable spotlights, 100W, outdoor use, Bluetooth control)

Website short text:

Brennenstuhl Professional tripod LED Work Light three-head 13050 T with 13500lm (LED Floodlight with 3 individually adjustable spotlights, 100W, for outdoor use, Bluetooth control)

Print short text:

Professional tripod LED construction spotlight three-head 13050 T, IP54, 13500lm, 5m H07RN-F 2X1.0

Bulletpoint 1:

Extremely powerful 360° LED Work Light with 13500lm is ideal for illuminating construction sites, enclosed spaces or halls - optimum lighting of the working environment with 360° beam angle

Bulletpoint 2:

Each of the three spotlight elements can be individually adjusted to achieve the right lighting position for every requirement - in addition, the entire spotlight head can be tilted and extended to a height of up to 2.2 metres

Bulletpoint 3:

The LED Floodlight has four switching levels 100% - 75% - 50% - 25% and 5m cable (H07RN-F 2X1.0) - Compact and fully collapsible tripod light (only 103cm long when folded) with 3 sturdy feet

Bulletpoint 4:

The IP54 construction site Worklight is designed for extremely demanding conditions - for use on construction sites in accordance with DGUV 203-006 (formerly BGI 608) and for permanent outdoor use

Bulletpoint 5:

Bluetooth control via the free BT Control app from Brennenstuhl - switching on and off, brightness setting, grouping (several work lights can be controlled simultaneously), as well as automatic switch-off via a countdown timer

**Online description:**

The Tripod LED Worklight three-head 13050 T from Brennenstuhl is ideal for illuminating construction sites, enclosed spaces or halls. Each of the three spotlights can be individually adjusted to achieve the optimum lighting position for every requirement. The Floodlight has a total of four switching levels (100% - 75% - 50% - 25%) and also impresses with the following features:

- * Bluetooth control via the free BT-Control app
- * Cable length: 5m (H07RN-F2x1.0)
- * Luminous flux: 13500lm
- * Power: 100W
- * Colour temperature: 6500K
- * Min. nominal input voltage: 220V
- * Max. Rated input voltage: 240V
- * High impact resistance: IK08
- * Protection class: II
- * Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts

Website description:

The Professional Tripod LED Worklight three-head 13050 T is ideal for illuminating construction sites, enclosed spaces or halls. Each of the three spotlights can be individually adjusted to achieve the optimum lighting position for every requirement. Numerous settings can be made using the free BT Control app: Switching on and off, brightness, grouping (several work lights can be controlled simultaneously) and setting a countdown timer. The construction Floodlight has a total of four switching levels (100% - 75% - 50% - 25%) and also impresses with the following features:

- * Cable length: 5m (H07RN-F2x1.0)
- * Luminous flux: 13500lm
- * Power: 100W
- * Colour temperature: 6500K
- * Min. rated input voltage: 220V
- * Max. Rated input voltage: 240V
- * High impact resistance: IK08
- * Protection class: II
- * Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts

Keywords:

work light, worklight, worklight brennenstuhl, brennenstuhl, led work light, work light tripod stand, work light tripod, work light with stand, led tripod work light, tripod work light, brennenstuhl floodlight, site light

Subtitle:

For use on construction sites in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use.

Print description:

- * Ideal for illuminating construction sites, enclosed spaces or halls.
- * Excellent all-round lighting thanks to 360° beam angle.
- * The three individual spotlight elements can be individually adjusted for an optimum lighting position.
- * The entire spotlight head can be tilted and extended to a height of up to 2.2 metres.
- * With four switching levels 100% - 75% - 50% - 25% .
- * Compact and fully collapsible tripod light (only 103 cm long when folded) with 3 sturdy feet.
- * Bluetooth control via the free BT-Control app from Brennenstuhl.
- * Functions include switching on and off, brightness setting, grouping (several spotlights can be controlled simultaneously) and automatic switch-off via a timer.
- * Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts.

Information text:**Table article information:****Scope of supply:**

Professional Tripod LED construction spotlight three-head 13050 T, 5m H07RN-F2x1.0

Product picture 1 and 2

/publicpictures/Produktbild/1173700008.tiff



Media

	/publicpictures/Logo-Extern/logo-bluetooth-blau-schwarz.eps	
	/publicpictures/Produktlinie/produktlinie-professional-coolgrey.eps	
	/publicpictures/Logo-Brennenstuhl/logo-engineered-in-germany.eps	
	/publicpictures/Logo-Brennenstuhl/logo-bt-control-app-kachel.eps	Additional functions via the BT-Control app * The additional functions (switching on and off, brightness setting, grouping and automatic switch-off via a countdown timer) can be controlled via the BT-Control app * Available in the App Store and Google Play Store
	/publicpictures/Icon/icon-stossfest-ik08.eps	IK08- Impact resistance grade * The impact resistance rating indicates how well a housing or device is protected against mechanical shocks and impacts * IK08 means that the device can withstand an impact energy of 5 joules, which corresponds to a blow with a 1.7 kg hammer from a distance of 30 cm
	/publicpictures/Icon/icon-schutzart-ip54.eps	Dust and splash-proof * Protection against contact and internal dust deposits * Also protected against splashing water from all directions
	/publicpictures/Icon/icon-kabellaenge-5m.eps	
	/publicpictures/Icon/icon-norm-dguv-i-203-006-k2-bgi-608.eps	For use on construction sites * For use on construction sites in accordance with DGVU 203-006 (formerly BGI 608) and permanent outdoor use * Category 2 equipment (K2 DGVU 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts



/publicpictures/Icon/icon-lumen-13500.eps



/publicpictures/Detailansicht/1173700008-1173700010-kopf-schwenkbar-2.tiff



/publicpictures/Detailansicht/1173700008-seite-eingeklappt.tiff



/publicpictures/Detailansicht/1173700008-kabelhalterung-bluetoothknopf-blau.tiff



/publicpictures/Anwendung/1173700010-anwendung-baustelle-schweissen.tif



/publicpictures/Anwendung/1173700010-anwendung-baustelle-strahler-einstellen-1.tif

Context

Attribute category:

Light

Accessories:

Garantie:

3 years

Spare part:

0172640176
0172640177



Similar products:

1173700010
9171410180

/publicpictures/Garantie/icon-garantie-3jahre-en.eps

Technical data

Kabel		Leuchte3Stecksystem	
Cable designation:	H07RN-F 2X1,0	Plug system plug:	Type E and F (Protective contact with earth hole)
Cable assembly:	H07RN-F		
Cable quality:	Rubber-Neoprene	Type of plug:	Straight plug
Number of cores:	2	Leuchte4Details	
Core cross section:	1mm ²	Hammer sign:	Yes
Protective conductor:	X	For "complicated conditions" (according to VDE):	Yes
Cable length:	5m	Leuchtmittel1Betriebseigenschaften	

Cable colour:	black	Colour rendering index:	80-89 (class 1B)
Cable entry into the housing:	Cable bend relief	Colour temperature:	6,500K
Useful cross section:	1mm ²	Mgv	
Leuchte0Allgemein		Packaging unit (UP):	1
Type of lamp:	Tripod floodlight	Weight of product (without packaging):	8.67kg
Housing material:	Plastic/ metal	Length of product (without packaging):	26cm
Surface finishing:	Matt	Width of product (without packaging):	21cm
Colour:	grey, black	Height of product (without packaging):	103cm
Colour cover:	transparent	Weight of product (including packaging):	10kg
Basic colour:	grey, black	Length of product (including packaging):	26.5cm
Lamp type included:	Yes	Width of product (including packaging):	22.5cm
Number of lamps:	3	Height of product (including packaging):	104cm
Direction of rotation:	Vertical/ horizontal		
Rotatable:	Yes		
Collapsible/ Bendable:	Yes		
With carrying handle:	Yes		
Height adjustable:	Yes		
Min. height adjustable:	103cm		
Max. height adjustable:	220cm		
Packaging:	In display packaging		
Adjustable colour temperature:	No		
Adjustable luminous flux:	Levels		
Luminous flux:	13,500lm		
Leuchte1elektrWerte			
Protection class:	II		
Power supply:	Mains operation		
Nominal frequency:	50/60 Hz		
Power consumption:	100W		
Power consumption in standby mode:	0W		
Min. Nominal input voltage:	220V		

Max. Nominal input voltage:	240V
Type of input voltage:	Alternating voltage (AC)
Leuchte2Anwendung	
With wireless control:	Yes
Radio standard:	Bluetooth
Compatibility:	other
Radio frequency:	2.4 GHz
Wireless range:	15m
Networkable:	Yes
Degree of protection (IP):	IP54
Suitable for outdoor area:	Yes
Impact strength:	IK08
Shock resistance:	Yes
K2:	Yes

Variant group

Professional Tripod LED construction spotlight three-head 13050 T

- * Ideal for illuminating construction sites, enclosed spaces or halls.
- * Excellent all-round lighting thanks to 360° beam angle.
- * The three individual spotlight elements can be individually adjusted for an optimum lighting position.
- * The entire spotlight head can be tilted and extended to a height of up to 2.2 metres.
- * With four switching levels 100% - 75% - 50% - 25% .
- * Compact and fully collapsible tripod light (only 103 cm long when folded) with 3 sturdy feet.
- * Bluetooth® control via the free BT-Control app from Brennenstuhl.
- * Functions include switching on and off, brightness setting, grouping (several spotlights can be controlled simultaneously) and automatic switch-off via a timer.
- * Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical impacts.

Related articles

1173700008

Variant differentiation

Country specification

Countries/ Languages: DE_de, ES_es, PL_pl, SE_se, CZ_cz, BE_fr_nl, DK_dk, FR_fr, HU_hu, NL_nl, RO_ro, SK_sk

